

Mrx Transport Monitor/Defibrillator Check List

Unit/Location:	
Device Number:	_
Procedure to Perform MRx Defib Test 1. Unplug Defib Pads from Therapy Cable 2. Plug Therapy Cable into Test Load 3. Power on Defibrillator/Monitor 4. Deliver 150J Shock into Test Load 5. Verify energy delivered is in range 6. Turn Off Defibrillator/Monitor 7. Re-connect Defib Pads to Therapy Cable	
RFU (Ready For Use) Indicator shows hourglass - If red "X" displayed, turn unit on and allow self-check to complete. If red "X" remains visible, call Service Center for Replacement and take unit out of service Therapy Cable Present	
Defibrillation Test Performed	-
Pre-connect Defibrillation Pads Present (2 sets)	
3 - Lead Monitor Cable Present	
Monitoring Electrodes Present (at least 6)	
Blood Pressure Cuff and Tubing Present & Connected	
Pulse Oxyemtry Cable/Probe Present	
Filterline H Set (End-Tidal CO2 Airway Adapters)	
Pulse Oxyemtry Cable/Probe Present	
QCPR Device Present	
QCPR Adhesive Pads Present	
Test Load Present	
Deviced Plugged in to Electrical Outlet for Charging	
Signature Initials	Signature Initials ———————————————————————————————————
Notes:	